



VOSKER V150

Solar Powered LTE Security Camera



Anywhere you need it.

The V150 is a 100% wireless and portable security camera equipped with VOSKER built-in solar panel technology. This LTE-based cellular security device is ideal for remote area photo surveillance where access to electricity and Wi-Fi network is impossible.



100% Wireless: Works Without Wi-Fi or Electricity



Automatic motion detection with custom alerts on the mobile app



Monitor job site, farm, cabin or any other remote locations



IP65 Certified Weather-Resistant



Built-in solar panel technology



Long lasting battery pack



Preactivated SIM card, SD card and mount included



FREE 7-day "ELITE" plan trial



Local photo backup on SD card



VOSKER two (2) year limited warranty.



For more information or to buy an international model, contact support@vosker.com



GENERAL SPECIFICATIONS - V150

PHOTO

Photo Resolution	FULL HD (1920 × 1080 px) local on SD card and 600 × 338 on mobile app
File Format	JPG
Multi-shot Mode	1 or 2 photos per detection
Information Stamped on Photos	Date, time and temperature (°C/°F)
Operation Mode	Photo
Capture Mode	Color photos by day, infrared by night
Angle View	43.6°

MEMORY

Capacity External Memory	Up to 32 GB (16 GB microSD card included)
---------------------------------	---

BATTERY/POWER SOURCE

Lithium Battery	Lithium rechargeable battery pack 10,000 mAh (V-LIT-B2) included
Power Jack	Micro-USB 5V

SOLAR SYSTEM

Solar Panel	Built-in solar panel
Internal Battery	No



GENERAL SPECIFICATIONS - V150

DETECTION SYSTEM

Detection System	PIR
Detection Angle	42°
Motion Sensor	1 sensor for a total of 5 detection zones
Detection Range	90 ft
Optional Delay Between Detections	Instant, 10s, 1 min, 3 min, 5 min, 10 min, 15 min and 30 min

NIGHT VISION/FLASH

LED	4 High Power LED
Night Vision Range	80 ft

DIMENSIONS

Camera Body	3.5" W × 3.8" D × 5" H (excluding the antenna)
--------------------	--



GENERAL SPECIFICATIONS - V150

CELLULAR

SIM Card	Included
Cellular Connectivity	LTE
Reception	Mobile App or Web App
Required Carrier	No specific carrier (Multi-Carrier)
Synchronization Frequency	1/day, 2/day, 6/day, 12/day or each detection
GPS Tracker	No
Camera Configuration	Web app or mobile app

GENERAL CONFIGURATION

Language	English, French, Spanish and German
Sensitivity Settings	Low, normal and high
Date Format	mm/dd/yyyy or dd/mm/yyyy
Photo Stamp Information	Yes (date/time, temperature)
Temperate Units	°C or °F
Time Format	12H or 24H



GENERAL SPECIFICATIONS - V150

OTHER

External Antenna	Included
External Extra Long Antenna	Sold separately
Port	5V-5A micro-USB Port
Mounting Bracket	Adjustable mounting arm
Operating Temperature Range	+50°C to -40°C
Certifications	FCC,CE, IP65 weather-resistant
Warranty	www.vosker.com/warranty-and-repair/